EUCO THX

ADMIXTURE FOR CEMENTITIOUS GROUTS



DESCRIPTION

EUCO THX is a powdered admixture for use in most types of grout mixes. It is designed to enhance cement-based grouts by allowing a reduction in mix water while enhancing flow. EUCO THX will also improve early and ultimate strength characteristics, minimize bleed water, minimize segregation and reduce or eliminate shrinkage.

PRIMARY APPLICATIONS

- · Contact grouting
- · Consolidation grouting
- · Mining applications
- · Anchoring grouts

FEATURES/BENEFITS

- · Reduces bleed water
- · Significant reduction in mix water
- Higher early and ultimate strengths
- Reduce or eliminate shrinkage
- Minimize segregation

PACKAGING

EUCO THX is available in 25 lb (11.4 kg) pails and 1,300 lb (590 kg) super sacs.

SHELF LIFE

6 months in original, unopened container.

SPECIFICATIONS/COMPLIANCES

EUCO THX meets or exceeds the requirements of ASTM C 937.

DOSAGE

EUCO THX is generally dosed at rates ranging from 2 to 6 lbs/100lbs (2 to 6 kg/100 kg) of cementitious material.

DIRECTIONS FOR USE

EUCO THX can be mixed into the mix independently or with any of the mix components. Ensure that it is thouroughly dispersed throughout the mix.

PRECAUTIONS/LIMITATIONS

- · Store in a dry place
- · Do not add other admixtures
- Not recommended for precision grouting applications
- In all cases, consult the Material Safety Data Sheet before use.

Additional Information

For more information on the use of EUCO THX, or any other Euclid Chemical product, contact The Euclid Chemical Company Mining and Tunneling Division at 1-800-321-7628, extension 8395.



The Euclid Chemical Company







